PRODUCT SPECIFICATIONS FOR QUICKFIT

Product Description

The QuickFit product is designed to give wall surfaces the look of Ledgestone in an easy-to-install, panelized unit. It is comprised of rectangular units that contain two or more stone “impressions”, and they are set in a uniform pattern with no grout line. The product is made by preparing a mixture of Portland cement, lightweight aggregate, water, and iron oxide color pigments. This mixture is then poured into molds and allowed to set overnight. Once the product is removed from the molds, it is allowed to cure for several days prior to shipment.

Product Sizing

Individual flat stone units are sized at 4” in height and either 8”, 10”, 12”, or 14” in length. Individual corner stone units are sized either 11” or 9” along the long leg, 3.5” along the short leg, and 4” in height. Stone units average 1¼” in thickness, but may range from 1” to 1¾” at the extremes.

Available Colors

The QuickFit product style is available in a limited selection of colors. The end-user must specify project-specific color selections.

Mortar Joint Options

The QuickFit product does not require a grout joint. It is always “drystacked”. While a mortar joint could potentially be used, it would essentially defeat the purpose of the panelized unit.

Packaging

Stone units are provided via shrink-wrapped pallets containing anywhere from 15 to 160 square feet of finished product. For small orders, color scheme elements may be interlaced at random or may be found in more or less distinct layers on the pallet(s). For large orders, color scheme elements are generally segregated with only one color per pallet.

Installation Tips & Techniques

The installation professional should contact Impressions in Stone prior to beginning work to discuss the color scheme prescribed by the end-user. In particular, the installation professional must learn the ratios of each element of the color scheme to achieve the desired final look. With the QuickFit style, it is important to avoid introducing a “wavy” pattern into the wall surface field. The Installation professional may wish to consider using chalk lines or other methods to ensure a straight, level pattern. If the end-user requires that a sealer be used, the installation professional must select a high-quality, breathable masonry sealer and apply it in strict accordance with the manufacturer’s instructions. Be advised that certain impregnating, hydrophobic sealers may actually LEAD to damage from freeze/thaw cycles, so review your options carefully.